

Gun Sprinkler

Code	Details	Picture	Box size/weight	Carton size (cm)	carton weight (kg)	Weight (kg/pc)	Remark
GS25	1" female thread connect Rotation angle: 0-360° (controled) Nozzle size: 5-6-7-9mm, flow rate: 2-6.5m³/h; Working pressure: 0.15-0.4MPa, Spray range: 12-19m		36.6*9.7*23.2cm 2.94kg	48*39*25	15.5	0.7	20pc/carton 4pc/box
GS30	1.5" female thread connect Rotation angle: 0-360° (controled) Nozzle size: 8-10-12-14-16mm flow rate: 5-25m³/h; working pressure: 0.15-0.5MPa, Spray range: 26-29m		36.6*9.7*23.2cm 3.14kg	48*39*25	16.28	1.5	10pc/carton 4pc/box
GS30B	1-1/4" female thread connect Rotation angle: 0-360° (controled) Nozzle size: 8-9-10-12-14mm, flow rate: 3.7-18.6m³/h; working pressure: 0.15-0.5MPa, Spray range: 16-29m		36.6*9.7*23.2cm 2.74kg	48*39*25	14.52	1.3	10pc/carton 4pc/box
GS35	Aluminum alloy base, copper water inlet, aluminum alloy rocker arm 1.5" female thread connect, Rotation angle: 0-360° (controled) Nozzle size: 10-12-14-16-18mm flow rate: 5-25m³/h; working pressure: 0.2-0.6MPa, Spray range: 18-36m		9.5*10.8*32.2 cm 3.64kg	57*51.5*34	19.35	3.16	5pc/carton 5pc/box

GS40	Copper base, stainless steel water inlet, rocker arm with shock absorber, 2" female thread connect, Elevation 24° Rotation angle: 0-360° (controled) Nozzle size: 12-14-16-18-20-22mm, flow rate10-40m³/h working pressure: 0.15-0.5MPa Spray range: 20-43m		60.7*8.1*32.2cm 3kg	63*43*34	16.36	2.66	5pc/carton 5pc/box
GSY40	Copper base, stainless steel water inlet, rocker with shock absorber, two-way water outlet, Rotation angle: 360 °whole spraying Nozzle size:12-14-16-18-20-22mm flow rate: 10-50.3m³/h; working pressure: 0.15-0.5MPa, Spray range: 20-46.5m			60*26*23.6		4.4	1pc/carton
GS40-43°	Copper base, stainless steel water inlet, rocker arm with shock absorber, 2" female thread connect, Elevation 43° Rotation angle: 0-360° (controled) Nozzle size:14-16-18-20-22mm flow rate: 17-52m³/h, working pressure: 0.3-0.8MPa Spray range: 26-55m, Spray height: 15-34m		60.7*8.1*32.2cm 3kg	63*43*34	16.36	2.66	5pc/carton 5pc/box
GSW40	1.5" female thread connect, Worm gear drive,, 24 ° elevation Rotation angle: 0-360° (controled) Nozzle size:12-14-16-18-20-22mm flow rate: 10-37m³/h working pressure: 0.2-0.5MPa Spray range: 22-41m			60*26*23.6		4.4	1pc/carton

GS50-24	Six hole flange interface, free counter flange, can weld 50-65-75-80mm pipe Ordinary rod length, 24 °, 43 °elevation optional Rotation angle: 0-360° (controled) Nozzle size16-30mm flow rate: 15-60m³/h; working pressure:0.2-0.7MPa, Spray range: 27-55m			85*22.2*27		8.38	1pc/carton
GS50L-24	Six hole flange interface, free counter flange, can weld 50-65-75-80mm pipe The length of the extension rod is 15cm longer than that of the other details as GS50-24			98*22.2*27		8.68	1pc/carton
GSN50	Six hole flange interface, free counter flange, can weld 50-65-75-80mm pipe Adjustable atomization effect, 24°elevation, Rotation angle: 0-360° (controled) Nozzle size: 4 from 16 to 30mm flow rate: 18-75m³/h; working pressure: 0.2-0.7MPa, Spray range: 26-53m			80.5*23*30.5		7.82	1pc/carton
GSC50	2" copper thread or 6-hole flange is optional, Adjustable speed is fast orslow, and atomization can be adjusted, 24 ° elevation Rotation angle: 0-360° (controled) Nozzle size: Choose 6 from 14 to 30 flow rate: 10-70m³/h, working pressure: 0.2-0.7MPa Spray range: 23-56m			86.5*22.2*28.5		8.7	1pc/carton
GS80	80 water inlet, adjustable speed, adjustable atomization, adjustable elevation 16-46° Nozzle size30-40mm, flow rate: 58-174m³/h; working pressure: 0.3-0.8MPa, Spray range: 37-80m			120*31*35		13.98	1pc/carton



Langfang Grain Agricultural Development CO.,LTD