


High Polymer PE Knitted Flat Hose



Product Category

1) Light Duty 2-3bar 2) Middle Duty 4-6bar 3) Heavy duty 8-10bar

Product advantages and selling points

High-strength polyester industrial filament and high-quality PVC

Soft leather, high pressure, easy to operate, Wear resistance, aging resistance, UV resistance, sun protection, Non-toxic, odorless, environmentally friendly (environmental-friendly hose can pass REACH and FDA testing standards)

Specification range: 3/4"-16" (19-406MM)

Temperature range: -10°C-65

1. This product is widely used, mainly used in agricultural irrigation, forestry sprinkler irrigation, construction engineering, industrial and mining industries and other fields
Ideal product for water supply and drainage.

2. Appearance color: mainly red, yellow, blue, green and purple, with beautiful and generous characteristics, and can also be rooted

According to user needs to produce colors.

3. Performance characteristics: the tube is soft and resistant to distortion; corrosion resistance, weak acid and weak alkali resistance; aging resistance, long use time;
Strong heat resistance, high strength; easy to stretch and roll, easy to move. The blasting pressure is high, non-toxic, tasteless and environmentally friendly.

4. Features of use: The length of the water pipe can be spliced arbitrarily when in use, it is convenient to move, strong maneuverability, and can be detached and occupied during storage.

The space is small, the roll is flat and easy to collect, the movement is convenient, the length is unlimited, it can be matched with the drought-resistant equipment of agricultural orchard, and it is equipped with aluminum

Buttons, plastic buttons, mechanical seals and various sprinkler irrigation units



Specification (Enhanced)

Item Code	I.D		W.P.		B.P.		Length	Weight
	inch	mm	psi	bar	psi	bar	m/roll	kg/m
PKF25	1"	25	145	10	435	30	50/100	0.05
PKF38	1.5"	38	130	9	390	27	50/100	0.07
PKF51	2"	51	115	8	345	24	50/100	0.08
PKF64	2.5"	64	108	7.5	324	22.5	50/100	0.10
PKF76	3"	76	108	7.5	324	22.5	50/100	0.12
PKF89	3.5"	89	95	6.5	285	19.5	50/100	0.14
PKF105	4"	102	87	6	261	18	50/100	0.16
PKF115	4.5"	115	87	6	261	18	50/100	0.18
PKF127	5"	127	72	5	216	15	50/100	0.19
PKF153	6"	153	58	4	174	12	50/100	0.22
PKF180	7"	180	43	3	129	9	50/100	0.29
PKF203	8"	203	36	2.5	108	7.5	50/100	0.35
PKF254	10"	254	29	2	87	6	50/100	0.42
PKF305	12"	305	15	1	45	3	50/100	0.52

Specification (Wear-resistant type)

Item Code	I.D		W.P.		B.P.		Length	Weight
	inch	mm	psi	bar	psi	bar	m/roll	kg/m
PKW25	1"	25	145	10	435	30	50/100	0.09
PKW38	1.5"	38	130	9	390	27	50/100	0.13
PKW51	2"	51	115	8	345	24	50/100	0.16
PKW64	2.5"	64	108	7.5	324	22.5	50/100	0.20
PKW76	3"	76	108	7.5	324	22.5	50/100	0.23
PKW89	3.5"	89	95	6.5	285	19.5	50/100	0.27
PKW105	4"	102	87	6	261	18	50/100	0.31
PKW115	4.5"	115	87	6	261	18	50/100	0.35
PKW127	5"	127	72	5	216	15	50/100	0.38
PKW153	6"	153	58	4	174	12	50/100	0.42
PKW180	7"	180	43	3	129	9	50/100	0.56
PKW203	8"	203	36	2.5	108	7.5	50/100	0.68
PKW254	10"	254	29	2	87	6	50/100	0.82
PKW305	12"	305	15	1	45	3	50/100	1.04